



**CBD20L AND CBD60L ELECTRIC PALLET TRUCK**

General	1	Model		CBD20L(EPS)	CBD60L	
	2	Power Type		Electric	Electric	
	3	Operation Type		Stand-on	Stand-on	
	4	Rated Capacity	kg	6000	6000	
	5	Load Centre	c(mm)	600	600	
Characteristic&Dimension	6	Tyre	Front /rear type	PU/PU	PU/PU	
	7		Front Wheel Size	mm	∅ 84×80 (Double wheel)	∅85×145
	8		Driving Wheel Size	mm	∅ 248×75	∅343×108
	9		Balance Wheel Size	mm	∅ 115×55	∅125×50
	10		Front/rear Number (X=drive)		4/1X+2	4/1X+2
	11	Overall Dimension	Overall Height	h1(mm)	1170	1375
	12		Lifting Height	h2(mm)	120	115
	13		Min. Height	h3(mm)	90	100
	14		Wheelbase	y(mm)	1569	1845
	15		Overall Length	l1(mm)	2465	2215
	16		Overall Width	b1(mm)	790	1012
	17		Fork Dimensions	l/e/s(mm)	1150/1200×170×75	1200×235×86
	19	e	Wa(mm)	2278	2100	
	20	Aisle Width for Pallet 1000*1200		Ast(mm)	2589	2828
21	Aisle Width for Pallet 800*1200		Ast(mm)	2568	2735	
Performance	22	Speed	Travel (laden/unladen)	km/h	10/11	7/8
	23		Lifting (laden/unladen)	mm/s	20/25	41/54
	24		Lowering (laden/unladen)	mm/s	40/30	54/45
	25	Steering Type		EPS	Hydraulic	
	26	Parking Brake Type		Electromagnetic / Regenerative	Electromagnetic	
	27	Max.Gradeability(Laden/unladen)		%	10/15	6/8
	28	Service Weight(include battery)		kg	875	1580
Power&Transmission	29	Motor	Drive Motor Type		AC	DC
	30		Drive Motor	kw	3	4
	31		Lift Motor Type		DC	DC
	32		Lift Motor	kw	1.2	6.3
	33	Battery	Voltage/Capacity		V/Ah	24/280