



## CDDRD10/CTDRD10 SINGLE COLUMN STACKER SPECIFICATION

Specification	1	Model		CDDRD10	CTDRD10	
	2	Operating Type		Walkie	Walkie	
	3	Leg Type and Mast Type		Narrow Leg & Single Stage	Straddle Leg & Single Stage	
	4	Power Type		Electric	Electric	
	5	Load Centre	mm	600	600	
	6	Wheels Type	mm	PU	PU	
	7	Wheel Base	mm	1052	1134	
	8	Wheel Quantity	mm	1D / 1B / 4F	1D / 1B /2F	
Dimensions	9	Standard Lift Height	mm	1600/1950mm	1600/1950mm	
	10	Lowered Fork Height	mm	90	55	
	11	Fork Size(length/width/thickness)	mm	1150(1220)/185/55	1070/100/40	
	12	Overall Length	mm	1634	1640	
	13	Overall Width	mm	790	940	
	14	Outside Width between Forks	mm	550/600/650/685	200—812	
	15	Inside Width between Forks	mm	180/230/280/315	0—612	
	16	Max Extend Height	mm	2055/2405	2055/2405	
	17	Mast Lowered Height	mm	2055/2405	2055/2405	
	18	Min.Turning Radius	mm	1262	1344	
	19	Min.Aisle Width for Pallets 800×1200	mm	1841	1894	
	20	Min.Aisle Width for Pallets 1000×1200	mm	1833	1936	
	21	Min.ground Clearance	mm	30	50	
Performance	22	Speed	Travel (Laden/unladen)	km/h	3/3.5	3/3.5
	23		Lifting (Laden/unladen)	mm/s	130/230	130/230
	24		Lowering (Laden/unladen)	mm/s	130/230	130/230
	25	Max.Gradeability	(Laden/unladen)	%	5/7	5/7
	26	Service Weight ( include battery )		kg	460	458
Driven	27	Motor	Driven Motor	kw	DC 0.63	DC 0.63
	28		Lift Motor	kw	DC 2.0	DC 2.0
	29		Steering Motor	kw	/	/
	30	Battery	Standard	V/Ah	24/70	24/70
	31	Controller	Manufacturer		CURTIS	CURTIS
	32	Brake			Electromagnetic/Regenerative	Electromagnetic/Regenerative